



SPECIFICATION SHEET:

PuK Lume sconce




PuK is a low-profile LED sconce with four different housing shapes and dynamic acrylic accents available in seven different colors. Two LED modules provide up and downlight and are extremely energy efficient, using just eight watts each. They are also lensed to reduce glare, can be dimmed, and have a life expectancy of 60,000 hours.

Related Fixtures

Perf Pendant



Schoolhouse Pendant



DS-105



For reference only. Options specified may change appearance.

Line drawing is
not available.

MANNING LIGHTING SPECIFICATION SHEET - PuK Lume sconce

Fixture	Width	Height	Extension	Lamping	Finish: Housing	Diffuser
W-101	6"	9"	2.5"	: 2L8M35	PP	AWH : ALG : ACR : ASB : APN : AMD : FMC
W-103	6"	8.5"	2.5"	: 2L8M35	PP	AWH : ALG : ACR : ASB : APN : AMD : FMC
W-105	6"	8.5"	2.5"	: 2L8M35	PP	AWH : ALG : ACR : ASB : APN : AMD : FMC
W-107	6"	8.5"	2.5"	: 2L8M35	PP	AWH : ALG : ACR : ASB : APN : AMD : FMC

Fixture Notes

- LED Specs: Total watts: 16, Total Lumens: 970, CRI: 85, CCT: 3500K, L70: 60,000 hours, IP65 rated. Each self-contained module is "plug and play" containing all drive electronics, heat sink, and diffuser.
- Dimming option available. Consult factory to configure for your equipment.
- UL and C-UL listed.

Lamp Specifications

2L8M35: (2) 8 watt TerraLUX linear LED modules, 3500K CCT, 85 CRI, 430 lumens with L70 of 60,000 hours. Each array is a standalone unit with integrated drive electronics, heat sink, and optics.

Finish Specifications

PP: Powder coat paint: Polyester resin powder coat paint finish.

Diffuser Options

- AWH: Satin Ice White
- ALG: Satin Ice Light Green
- ACR: Cherry Red
- ASB: Sky Blue
- APN: Pine
- AMD: Mandarin
- FMC: Digital Mica

To Specify

- 1) Choose a finish for the Housing
- 2) Choose a lamping option
- 3) Choose a voltage option
- 4) Choose a diffuser

Sample: W-107-PP(WH)-2L8M35-FMC

[Click here to build a custom specification sheet.](#)